

**AMENDMENTS TO THE CLAIMS:**

---

1. (Amended) A pusher assembly for use in a contact block assembly, said pusher assembly comprising:

a body portion having an open top end defining an interior recess;

a first window formed in said body portion;

a second window formed in said body portion adjacent to said first window, said second window being larger than said first window to define a shoulder;

A2 a spring received in the recess through the top end; and

a movable contact positioned within said second window captured between the spring and the shoulder.

[Please cancel claims 2 and 3.]

4. (Rewritten) A pusher assembly for use in a contact block assembly, said pusher assembly comprising:

a body portion;

a first window formed in said body portion;

a second window formed in said body portion adjacent to said first window, said second window being larger than said first window; and

a movable contact positioned within said second window,

wherein said first window and said second window are formed in a first portion of said body portion and a recess is formed in said first portion of said body portion, wherein said recess formed in said first portion of said body portion further extends to a second portion of said body portion.

A2  
cont  
5. (Amended) The pusher assembly of claim 4 further comprising a spring positioned within said recess.

6. (Rewritten) A pusher assembly for use in a contact block assembly, said pusher assembly comprising:

a body portion;

a first window formed in said body portion;

a second window formed in said body portion adjacent to said first window, said second window being larger than said first window; and

a movable contact positioned within said second window,

wherein said first window and said second window are formed in a first portion of said body portion and a recess is formed in said first portion of said body portion, and a spring is positioned within said recess and further comprising shoulders between said first window and said second window.

A3  
17. (Amended) A pusher assembly comprising:

A3  
Cont  
a body portion;

a recess means formed in said body portion for receiving a spring through an open top end of the body portion means;

a first window means formed in said body portion for receiving a movable contact;

a second window means formed in said body portion for retaining said movable contact.

18. (Amended) A method for assembling a pusher assembly, said method comprising the steps of :

inserting a movable contact into a first position in a first window through a pusher;

moving said movable contact to a second window through said pusher; and

rotating said movable contact to a second position within said second window.

---

#### REMARKS

Claims 1 and 4-32 are pending in the application, claims 2 and 3 being cancelled by this amendment. Claims 15 and 16 are allowed. Claims 4, 6-8, 11 and 13 are objected to. Claims 4 and 6 are rewritten in independent form so that claims 4-8 should now be allowed.